

Fuse-link, low voltage, 10 A, AC 600 V, DC 300 V, 300 kA, 21 x 57 mm, J, UL, with indicator, time-delay



Powering Business Worldwide™

Part no. INDICATING LPJ-10SP
Catalog No. LPJ-10SPI

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	10
Rated voltage			AC 600 V DC 300 V
Size			21 x 57 mm
Utilization category			J
Status indicator			with indicator
Breaking Capacity		kA	300
Release characteristic	class		time-delay
Standard/Approval			UL
Shape			cylindrical centre-bolted tags
Standards/Regulations			Not Applicable
Time delay			time-delay 10 seconds (minimum) at 500% of rated current

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			Other
Nominal rated current		A	10
Nominal rated voltage		V	600
Utilization category			Other
Type of fuse status indicator			Centre fuse status indicator