







## M22520/1-07 **TP85**

USE WITH M22520/1-01 BASIC TOOL



MS18232 & MS18233 **OUTER PIN & SOCKET RG178/U & RG196/U CABLES** CRIMP AT SELECTOR No. 7

## **DATAPLATE**

	MATERIAL		ITEM	P/	PART NO.		QTY.	DESCRIPTION / REMARKS		
	N	N/A			DATE 5/28/2004 DATE	P		DANIELS MANUFACTURING CORP. ORLANDO, FLORIDA CAGE 11851		
RESTRICTED & CONFIDENTIAL	HEAT TREAT	NOTE				TITLE		N HEAD		
CONFIDENTIAL PROPERTY OF DANIELS MANUFACTURING CORP. NOT TO BE DISCLOSED TO OTHERS. REPRODUCTION OR USED FOR ANY OTHER PURPOSE EXCEPT AS AUTHORIZED IN WRITING BY DANIELS MANUFACTURING. MUST BE RETURNED TO DANIELS MANUFACTURING CORP. ON COMPLETION OF ORDER OR PURPOSES FOR WHICH LENT.	N	W/ / I	THIS DRAWING IS AN OUTLI DRAWING OF THE RESPECTI DMC PART NUMBER			WHERE I	used: <b>AF8</b>	(M22520/1-0	7)	
CREATED FROM AN INVENTOR MODEL. CHANGES MUST BE REFLECTED IN THE 3D PART	FINISH N/A		INDICATED. ACTUAL DMC PART NUMBER IS CAD PART NUMBER WITHOUT			SIZE	SCALE	TP85-ENV	SHEET 1 C	
DO NOT SCALE DRAWING			TH	HE "-ENV" SU	-ENV" SUFFIX		2:1	TP85		REV.

## **LOCATOR** HOLE **ADDITIONAL FEATURES DIMENSIONS** Ø.109 ∟JØ.136 ▼.275 ₹.580

## **UNCONTROLLED DOCUMENT WILL NOT BE UPDATED**

**DIMENSIONS IN INCHES - UNLESS OTHERWISE SPECIFIED**