



## MQDC2S-1206

### ▶ SINGLE-ENDED CORDSETS



Cordset Power and I/O  
 Sealed 12-pin Euro-style QD  
 to flying leads - High Flex  
 Cable length: 2 m (6 ft)  
 Part Number: 11420

### SPECIFICATIONS

|                               |                     |
|-------------------------------|---------------------|
| Number of Contacts            | 12                  |
| Number of Connectors          | 1                   |
| Cable Jacket Material         | PVC                 |
| Cable Jacket Color            | Black               |
| Connector Body Material/Color | PVC Black           |
| Outside Cable Diameter (mm)   | 7.5                 |
| Cordset Length (m)            | 1.83                |
| Trunk Length (m)              | No Trunk            |
| Shield/No Shield              | Shield              |
| Shield Type                   | Open                |
| Coupling Material/Color       | Nickel Plated Brass |
| Maximum Temp. (°C)            | 105                 |
| Current Rating (A)            | 2.7                 |
| Minimum Temp. (°C)            | -40                 |
| Voltage Rating (V)            | 250 V ac/300 V dc   |
| IP Rating                     | IP67                |

|                                     |                |
|-------------------------------------|----------------|
| <b>Primary Connector Type</b>       | EURO           |
| <b>Primary Coupling Method</b>      | M12 Single Key |
| <b>Primary Gender</b>               | Female         |
| <b>Primary Orientation</b>          | Straight       |
| <b>Primary Number of Conductors</b> | 12             |
| <b>Primary AWG</b>                  | 20, 24         |
| <b>Secondary Connector Type</b>     | Flying Leads   |
| <b>Feature: Hazardous Area</b>      | No             |
| <b>Oil/Grease Resistant</b>         | No             |



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America