



Fuse-link, high speed, 200 A, AC 690 V, 200 kA, DIN 00, aR, DIN, IEC, type T indicator, live gripping lugs



Part no. FUSE 200A 690V 00TN/80 AR UR  
 Catalog No. 170M2667

### Delivery program

|                              |   |    |   |
|------------------------------|---|----|---|
| Product range                |   |    | Fuse  |
| Basic function               |   |    | Fuse-link                                     |
| Field of application         |   |    | high speed                                    |
| Rated current                | I | A  | 200   |
| Rated voltage                |   |    | AC 690 V                                      |
| Construction size            |   |    | DIN 00  |
| Utilization category         |   |    | aR  |
| Status indicator             |   |    | type T indicator                              |
| Description                  |   |    | live gripping lugs                            |
| Breaking Capacity            |   | kA | 200   |
| usable for size/applications |   |    | semiconductor protection                      |
| Standard/Approval            |   |    | DIN<br>IEC                                    |
| Shape                        |   |    | square body with offset bolted tags (slotted) |
| Standards/Regulations        |   |    | DIN 43653<br>IEC 60269-4                      |

### Technical data ETIM 8.0

|  |  |    |   |
|--|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)  |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |  |    |   |
| Fuse construction type according to IEC 60269  |  |    | 00  |
| Type of current  |  |    | AC  |
| Rated voltage AC   |  | V  | 690                                       |
| Rated voltage DC   |  | V  |   |
| Rated current  |  | A  | 200                                       |
| Utilization category   |  |    | aR (accompanied semiconductor protection) |
| Breaking capacity  |  | kA | 200                                       |
| Colour code  |  |    | None                                      |
| Type of fuse status indicator  |  |    | Top fuse status indicator                 |
| Power loss at rated current  |  | W  | 35  |
| Mounting holes   |  |    | M10                                       |
| Centre-to-centre distance of connections   |  | mm | 78  |

### Additional product information (links)

|                                      |   |
|--------------------------------------|---|
| High-speed full-line catalogue (pdf) | <a href="http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf">http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf</a> |
|--------------------------------------|---|